

R-2 W, 3000K Rail-Light

Specifications		
Optics	Light source	3000K
	LEDs expected lifetime	50,000 hours*
	Interchangeable lens option	25° / 35°
Photometric	Light output	3000lm
	Optical efficacy	115 lm/W
	CRI	>80
Features	Pan/Tilt	330° / 270°
Electrical	AC Power nominal	100 - 240 V 50/60 Hz
	AC Power max rating	90-264V 50/60Hz
	Maximum power consumption	32W
	Typical power consumption	28W
	Power factor	0.90 PF (230 V)
Programming and Control	Protocol	CRMx, W-DMX™ G2, W-DMX™ G3, W-DMX™ G4, W-DMX™ G4S
	Setting and addressing	Wireless DMX (LumenRadio) Software upgradable via wireless
	DMX channel	1
Physical	Dimensions (L x W)	224 x 187 mm (8,8 x 7,4 in)
	Spot diameter	Ø 104 mm (4,1 in)
	Weight	1 kg (2,2 lbs.)
	Material	Aluminium, Stainless steel, ABS
	Lens	PMMA
	IP class	IP20
Installation	Mounting	3-circuit track system
	Compatibility	Staff, Norlux, Global, Nuco and Nordic
	Orientation	Any
Thermal	Temperature range, Operating	-10° to +40°C (-14° to +104°F)
	Humidity (max.)	95%
	Cooling	Passive cooling
Connections	Power	Track mount adapter
	DMX	Wireless (Lumen Radio)
Conforms to	2006/95/EC: Low Voltage Directive	EN 60598-1, EN 60598-2-1, EN 60598-2-17, EN 62471
	1999/5/EC: R&TTE Directive	EN301489-1, EN301489-3, EN300328
	RoHS2 Directive	2011/65/EU
Included Items	Included Items	User manual
Fixtures and Accessories	Fixtures	Order no: 84010101 - R-2 W, 3000K, white, 25 deg Order no: 84010102 - R-2 W, 3000K, black, 25 deg
	Accessories	Order no: 83062011 - SGM USB uploader cable Order no: 80070229 - Lumen Radio transmitter DMX (Only)

*(Figure provided by manufacturer and obtained under manufacturer's test conditions)